

## Interface between modem and subscriber interface module (SIM)

Publication number: CN1429462

Publication date: 2003-07-09

Inventor: IV J A HUTCHISON (US); SUTANKAYO S I (US)

Applicant: QUALCOMM INC (US)

Classification:

- international: **H04L29/10; H04B7/26; H04M1/725; H04M11/06;**  
**H04L29/10; H04B7/26; H04M1/72; H04M11/06; (IPC1-**  
**7): H04Q7/32**

- European: H04M1/725; H04M11/06

Application number: CN20018007771 20010202

Priority number(s): US20000180228P 20000204

Also published as:



WO0158191 (A3-corr)

WO0158191 (A3)

WO0158191 (A2)

EP1252784 (A0)


CA2409816 (A1)

Report a data error here

Abstract not available for CN1429462

Abstract of corresponding document: **WO0158191**

A circuit for interfacing a modem in a wireless communication device to a Subscriber Interface Module (SIM) (122) includes a modem controller (302), a Universal Asynchronous Receiver/Transmitter (UART) (312) connected to the modem controller, a programmable clock circuit (314, 316) adapted to generate a SIM clock and a UART clock independently of one another based on a common clock (350) and a control signal (352) provided to the programmable clock circuit, a reset circuit (320) to generate a SIM reset signal, and a power control circuit (308) to control powering on and off the SIM, all on an integrated circuit chip (301). The circuit also includes a Bus Interface circuit (214) to interface the modem to the SIM using a common data line (212).



Data supplied from the [esp@cenet](mailto:esp@cenet) database - Worldwide